

Express Mail Label No. EL671852630US

PATENT APPLICATION
Docket No. 2983.2.1

UNITED STATES PATENT APPLICATION

of

John Spinks

and

Glenn M. Stephens

for

**NETWORK RESOURCE LOCATION DETECTION PROBE
APPARATUS AND METHOD**

Patent Application No. 2983.2.1

5 BACKGROUND

1. Related Inventions

This application is a Continuation of and claims priority to co-pending United States Provisional Patent Application Serial Number 60/178,581, filed on January 18, 2000, which is incorporated herein by reference.

10 2. The Field of the Invention

The invention relates generally to computer systems, and more specifically to methods and apparatus for physically locating and tracking devices connected to a network from a central point using the network cable infrastructure to which the devices connect.

15 3. Background

The computer age has advanced from analog computers having hard-wired program instructions up through programmable digital computers, and now highly networked programmable digital computers sharing information and applications across the world. With the advent of the computer as a business tool, nearly every profession now requires access to a computer in order to properly complete the daily routine of a job. Most of these computers are networked to share information and resources.

20 A computer network generally includes a number of intelligent network infrastructure devices, including without limitation switches, routers, hubs, and others, connected so as to allow communication among other network devices and end station devices, such as personal computers ("PCs"), servers, printers, scanners, fax machines, and the like. As the need for

5 access to computer resources grows the number and size of networks grow. The devices
comprising today's computer networks may constitute significant resource investments for
the organizations that sponsor and manage such networks. Accordingly, such organizations
have an inherent interest in maintaining an inventory of all devices comprising organizational
networks. Moreover, constant advances in technology demand ongoing upgrades to both
10 network hardware and software. To keep up with such technology advances, an organization
must maintain an inventory of the current hardware and software configurations connected
to its networks.

Past approaches to collecting information regarding network devices and software
suffer from several distinct disadvantages. For example, many organizations perform
inventories of network devices by conducting "walk around audits." This is a common
practice whereby organizations send people around their organization to determine the
physical locations of PCs and other network-based information technology equipment. The
information gathered in such "walk around audits" is often entered into a database to
facilitate future reference. Although walk around audits may result in a fairly complete and
20 accurate snapshot of a network's hardware and software configurations, such audits are very
resource-intensive, typically requiring a great deal of human time and effort for completion.
The information garnered in such walk around audits typically also quickly becomes obsolete
due to the movement, addition, and deletion of both hardware and software connected to the
network.

25 Walk around audits also typically include only an inventory or listing of devices
connected to a network and software installed on those devices without any kind of

5 designation or map of the physical location of the devices connected to the network. In view
of the foregoing, the information technology staffs of most organizations typically possess
device and software inventories that are out of date and are, therefore, incomplete due to
movement of devices as well as additions and deletions of both network devices and software
installations. Moreover, the IT staffs of these organizations typically do not possess up to
10 date maps or diagrams showing accurate associations between physical locations at which
networks are installed and the physical layout of network devices at such physical locations.

Based on the foregoing, it is clearly desirable to have a network information
collection mechanism that can maintain an accurate inventory of all hardware device
connected to a network and all software installed on those network devices.

It is also desirable to have a network information collection system that associates the
physical layout of the sites at which a network is installed with the physical network devices
and structural cabling comprising the network.

It is also desirable to have a network information collection system that can detect
changes in the network, including without limitation movement of devices, addition of
20 devices, removal of devices, and changes in software installations and configurations.

What is needed is a new method and apparatus for obtaining inventories of network
devices and software installations. Particularly, what is needed is a system capable of
obtaining and maintaining over time an accurate inventory of all devices connected to a
network and software installed on those devices, including without limitation the physical
25 location of each device connected to the network.

5

BRIEF SUMMARY AND OBJECTS OF THE INVENTION

In view of the foregoing, it is a primary object of the present invention to provide a method and apparatus having the capability to positively identify the physical location, as well as the configuration, of computer hardware and software by means of remote probing over known routes of physical connecting lines.

10

Consistent with the foregoing objects, and in accordance with the invention as embodied and broadly described herein, an apparatus and method are disclosed, in suitable detail to enable one of ordinary skill in the art to make and use the invention. In certain embodiments, an apparatus and method in accordance with the present invention may include software, hardware, firmware, or any combination thereof to implement the process of the invention.

15

This invention associates the physical location of a network connected device to its first connection to an intelligent network infrastructure device such as a switch, router, or hub. Further, this invention provides a method of tracking movement of network devices by observing changes in connection information in said devices. Such association is possible, because inter-office connections typically use structured cabling, which is permanent and diagramed, whereas network devices (such as PCs) are frequently moved within an organization.

20

25

The end point connection information for every device on the network is obtained by each PC on the network accessing its nearest network infrastructure device to obtain the end point connection information about itself and any other local devices to itself on the network. this information is then returned to a central database.

5

The information in the central database can then be associated by the system administrator to physical locations within the building (*e.g.* Floor 1, office 1-Sales).

Further, as network devices are relocated within the building this information is continually tracked and the new location information is automatically updated to reflect the new end point.

10

In certain embodiments, an apparatus in accordance with the present invention may include a reporting module, typically hosted on a PC connected to a network, that is capable of querying an intelligent network infrastructure device, such as a switch, a router, or a hub, to obtain end point connection information corresponding to the PC. The apparatus may also include a correlation module capable of associating the end point connection information acquired by the PC to a location identifier corresponding to the physical location at which the PC is actually installed at the physical site of the network. The end point connection information obtained by the PC may simply be the port number of the network infrastructure device to which the PC is connected via structural cabling.

20

The reporting module may transmit the end point connection information to a central database hosted on a server computer connected to the network. The reporting module may also include an update module capable of detecting changes in end point connection information corresponding to a PC connected to the network, which changes may be occasioned by movement of the PC from one location to another on the network or removal of the PC from the network.

25

The reporting module may also include an inventory module capable of detecting other network devices, such as printers or scanners, connected to the network and local to a

PC or workstation connected to the network, which may obtain end point connection information on behalf of the other network devices. The apparatus may also include a monitoring module, which is typically hosted on the server computer, capable of receiving end point connection information from reporting modules, typically hosted on network PCs or workstations.

The correlation module may also include a matching module capable of matching software license records to the software installed on devices connected to the network to determine whether the organization has sufficient software licenses to cover actual software installations on the network. Moreover, the correlation module may include a device recognition module capable of identifying the nomenclature of devices connected to the network. The inventory module may also be capable of detecting software and hardware configuration information of all devices connected to the network.

A method in accordance with the invention may include the steps of querying a network infrastructure device to obtain end point connection information corresponding to a PC or workstation connected to the network, reporting the end point connection information to a central database, and associating the end point connection information corresponding to the PC or workstation to a location identifier corresponding to a physical location at which the PC or workstation is then presently installed.

The central database may include device records storing end point connection information corresponding to devices connected to the network. The method may also include the steps of detecting a change of end point connection information corresponding to the PC or workstation and updating the central database to reflect the change.

5 The method may also include the steps of detecting a network device local to the PC
or workstation and obtaining end point connection information corresponding to the network
device local to the PC or workstation. The method may also include the step of matching
software license records to software applications installed on devices connected to the
network to determine the organization's legal compliance with applicable licensing
10 requirements.

The method may further include the step of identifying the nomenclature of devices
connected to the network based on product recognition records stored in the central database.
The method may also include the step of detecting software and hardware configuration
information corresponding to devices connected to the network. The method may include
the step of transmitting the software and hardware configuration information corresponding
to devices connected to the network to the central database.

BRIEF DESCRIPTION OF THE DRAWINGS

The foregoing and other objects and features of the present invention will become
20 more fully apparent from the following description and appended claims, taken in
conjunction with the accompanying drawings. Understanding that these drawings depict
only typical embodiments of the invention and are, therefore, not to be considered limiting
of its scope, the invention will be described with additional specificity and detail through use
of the accompanying drawings in which:

25 Figure 1 is a schematic block diagram of one architecture for a hardware suite
suitable for implementing an apparatus in accordance with the present invention;

5 Figure 2 is a schematic block diagram of various configurations of network devices connected to a network at a selected site, along with implementation schemes for implementing apparatus and methods in accordance with the invention;

 Figure 3 is a schematic block diagram of a network connection table of a network infrastructure device corresponding to an illustrated configuration of a typical network;

10 Figure 4 is a schematic block diagram illustrating the mapping of a physical site at which a network is installed to a schematic depicting the network installed at the physical site;

 Figure 5 is a schematic block diagram of data structures suitable for implementing at least one embodiment of an apparatus and method in accordance with the present invention;

 Figure 6 is a schematic block diagram of an administration computer hosting selected data structures in accordance with the invention;

 Figure 7 is a schematic block diagram of a node device hosting selected data structures in accordance with the invention;

20 Figure 8 is a chart illustrating one embodiment of an infrastructure database including infrastructure records in accordance with the invention;

 Figure 9 is a chart illustrating one embodiment of device record bound to a location identification in accordance with the invention;

 Figure 10 is a chart illustrating one embodiment of a binding table for mapping
25 device identification numbers to location identifications in accordance with the invention;

5 Figure 11 is an elevation view of one embodiment of a computer interface for binding infrastructure records to device records in accordance with the invention;

 Figure 12 is a schematic block diagram of one embodiment of a process for binding infrastructure records to device records and tracking changes to those bindings in accordance with the invention;

10 Figure 13 is a schematic block diagram of one embodiment of the step of ascertaining end point connection information of Figure 12 in accordance with the invention;

 Figure 14 is a schematic block diagram of one embodiment of the step of binding end connection information to physical location information of Figure 12 in accordance with the invention; and

15 Figure 15 is a schematic block diagram of one embodiment of the step of tracking device movements of Figure 12 in accordance with the invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

20 It will be readily understood that the components of the present invention, as generally described and illustrated in the Figures herein, could be arranged and designed in a wide variety of different configurations. Thus, the following more detailed description of the embodiments of the system and method of the present invention, as represented in Figures 1 through 15, is not intended to limit the scope of the invention, as claimed, but it is merely representative of the presently preferred embodiments of the invention.

25 The presently preferred embodiments of the invention will be best understood by reference to the drawings, wherein like parts are designated by like numerals throughout.

5 Those of ordinary skill in the art will, of course, appreciate that various modifications to the details illustrated in the schematic diagrams of Figures 1-15 may easily be made without departing from the essential characteristics of the invention. Thus, the following description is intended only as an example, and simply illustrates one presently preferred embodiment consistent with the invention as claimed herein.

10 Referring now to Figure 1, an apparatus 10 may include a node 11 (client 11, computer 11) containing a processor 12 or CPU 12. The CPU 12 may be operably connected to a memory device 14. A memory device 14 may include one or more devices such as a hard drive 16 or non-volatile storage device 16, a read-only memory 18 (ROM) and a random-access (and usually volatile) memory 20 (RAM).

15 The apparatus 10 may include an input device 22 for receiving inputs from a user or another device. Similarly, an output device 24 may be provided within the node 11, or accessible within the apparatus 10. A network card 26 (interface card) or port 28 may be provided for connecting to outside devices, such as the network 30.

20 Internally, a bus 32 (system bus 32) may operably interconnect the processor 12, memory devices 14, input devices 22, output devices 24, network card 26 and port 28. The bus 32 may be thought of as a data carrier. As such, the bus 32 may be embodied in numerous configurations. Wire, fiber optic line, wireless electromagnetic communications by visible light, infrared, and radio frequencies may likewise be implemented as appropriate for the bus 32 and the network 30.

25 Input devices 22 may include one or more physical embodiments. For example, a keyboard 34 may be used for interaction with the user, as may a mouse 36. A touch screen

38, a telephone 39, or simply a telephone line 39, may be used for communication with other devices, with a user, or the like.

Similarly, a scanner 40 may be used to receive graphical inputs which may or may not be translated to other character formats. A hard drive 41 or other memory device 14 may be used as an input device whether resident within the node 11 or some other node 52 (e.g., 52a, 52b, etc.) on the network 30, or from another network 50.

Output devices 24 may likewise include one or more physical hardware units. For example, in general, the port 28 may be used to accept inputs and send outputs from the node 11. Nevertheless, a monitor 42 may provide outputs to a user for feedback during a process, or for assisting two-way communication between the processor 12 and a user. A printer 44 or a hard drive 46 may be used for outputting information as output devices 24.

In general, a network 30 to which a node 11 connects may, in turn, be connected through a router 48 to another network 50. In general, two nodes 11, 52 may be on a network 30, adjoining networks 30, 50, or may be separated by multiple routers 48 and multiple networks 50 as individual nodes 11, 52 on an internetwork. The individual nodes 52 may have various communication capabilities.

In certain embodiments, a minimum of logical capability may be available in any node 52. Note that any of the individual nodes 52 may be referred to, as may all together, as a node 52 or nodes 52.

A network 30 may include one or more servers 54. Servers may be used to manage, store, communicate, transfer, access, update, and the like, any number of files for a network 30. Typically, a server 54 may be accessed by all nodes 11, 52 on a network 30.

5 Nevertheless, other special functions, including communications, applications, and the like may be implemented by an individual server 54 or multiple servers 54.

In general, a node 11 may need to communicate over a network 30 with a server 54, a router 48, or nodes 52. Similarly, a node 11 may need to communicate over another network (50) in an internetwork connection with some remote node 52. Likewise, individual
10 components of the apparatus 10 may need to communicate data with one another. A communication link may exist, in general, between any pair of devices or components.

By the expression "nodes" 52 is meant any one or all of the nodes 48, 52, 54, 56, 58, 60, 62, 11. Thus, any one of the nodes 52 may include any or all of the component parts illustrated in the node 11.

15 The directory services node 60 provides the directory services as known in the art. Accordingly, the directory services node 60 hosts the software and data structures required for providing directory services to the nodes 52 in the network 30 and may do so for other nodes 52 in other networks 50.

The directory services node 60 may typically be a server 54 in a network. However,
20 it may be installed in any node 52. To support directory services, a directory services node 52 may typically include a network card 26 for connecting to the network 30, a processor 12 for processing software commands in the directory services executables, a memory device 20 for operational memory as well as a non-volatile storage device 16 such as a hard drive 16. Typically, an input device 22 and an output device 24 are provided for user interaction
25 with the directory services node 60. In general, any number of workstation nodes 58, 62 may

5 exist in a network 30, within some practical limit. Any network 30, 50 may be part of, and connect to the Internet 64.

Referring now to Figure 2 while continuing to refer to Figure 1, a system 70 may be installed at a network site 72, which may be an office or building belonging to an organization or the like. The system 70 may include several nodes 74 having any or all of the attributes of a node 11 discussed hereinbefore. The nodes 74 may be personal computers (PCs) 74 or workstations 74. In the depicted embodiment, each node 74 operably connects to an intelligent network infrastructure device 76 via a structural cabling segment 78 and a network connection 82 or a jack 82. In the depicted embodiment, each structural cabling segment 78 also operably connects to a distinct port 80 of the network infrastructure device 76. A network infrastructure device 76 may be any intelligent network device including without limitation a switch, a router, a hub, or the like.

The network infrastructure device may also operably connect to a network 30, which in turn may operably connect to a network 50 in any configuration, as described hereinbefore. The network 30 may include an admin computer 84, which may be a server 54, as described hereinbefore. The admin computer 84 preferably operably connects to the network 30, and to the nodes 74 through the network 30. The admin computer 84 may host an admin module 86, which may provide selected functionalities in accordance with the invention. Individual nodes 74 may host a reporting module 88 for gathering and providing selected information via the jacks 82 and structural cabling 78 to the admin module 86 of the admin computer 84 in accordance with the invention.

5 A system 70 may also include other network devices 90, such as network printers 92,
network scanners 94, and the like. A system 70 may also include one or more standalone
nodes 96 or standalone PCs 96. Like individual network nodes 74, individual standalone
nodes 96 may host a reporting module 88, which may gather selected information pertaining
to individual nodes 96 and operably connected devices to be reported to the admin computer
10 84 via removable media, such as a floppy diskette or the like. Moreover, a system 70 may
include one or more mobile nodes 98 or mobile PCs 98, which may also individually host
a reporting module 88. Mobile nodes 98 may connect to the network infrastructure device
76 via a dial-up connection or the like. The reporting module 88 of a mobile node 98 may
gather selected information pertaining to the hosting mobile node 98 and operably connected
15 devices to be reported to the admin computer 84, when the mobile node 98 operably connects
to the network infrastructure device 76 via dial-up connection or the like.

Referring to Figure 3 while continuing to refer to Figures 1 and 2, one embodiment
of a system 70 is shown that includes eight nodes 74 connected to a network infrastructure
device via jacks 82, structural cabling 78, and ports 80. As shown in the depicted
embodiment, a network infrastructure device 76 may maintain end point connection
20 information 100 in a connection table 100 including port numbers 102 bound to node
identification numbers 104. In other words, in the depicted embodiment, the connection
table 100 tracks by identification number which nodes are operably connected to each port
80 of the network infrastructure device 76.

25 Typically, network infrastructure devices, such as device 76, each have a processor
and memory capable of storing status variables and other values in memory that are

continuously changed and updated as such devices operate. The status of a network infrastructure device 76 may be ascertained by transmitting a message requesting information over the network to a software program or agent running on the target device 76. In response, the agent may send a message over the network to the requesting station. Such communications are typically carried out according to an agreed-upon protocol, such as the Simple Network Management Protocol (SNMP).

Accordingly, in the depicted embodiment, the reporting module 88 of any node 74 may transmit a message, typically using SNMP, to obtain the information contained in connection table 100. A reporting module 88 hosted on a node 74 may then use information from the connection table 100 to determine to which port 80 and structural cabling 78 the particular node 74 is connected. In other words, the reporting module 88 of a node 74 may function to determine the “end point connection” information corresponding to the hosting node 74 and any other network devices 90 local to the node 74. The reporting module 88 of a node 74 may then report the “end point connection” information corresponding to the node 74 and other local network devices 90.

Referring to Figure 4 while continuing to refer generally to Figures 1-3, the physical layout of a network site 72 may be mapped 106 to the structural layout 107 of the structural cabling 78 of a computer network, such as a network 30. In the depicted embodiment, the map 106 of the network site 72 includes physical network connections 82a-i or jacks 82a-i and network physical locations 108a-h. As shown in Figure 4, the physical layout 105 of a network site 72 may be associated with or mapped to the schematic and physical layout of structural cabling 78 of a network 30 or portion of a network 30 installed at a network site

5 72. Of course, since the structural cabling 78 installed at the network site 72 is connected,
either directly or indirectly, to one or more network infrastructure devices 76, a port 80 of
a network infrastructure device 76 may be identified as corresponding to each physical
network connection 82 physically installed at the network physical locations 108.

10 The scope of the invention is as broad as generally described above. The illustrations
contained in Figures 5-15 are merely representative of certain, presently preferred
embodiments of the invention and should not be interpreted to be limiting of the scope of the
invention broadly described above. Those presently preferred embodiments of the invention
will be best understood by reference to Figures 5-15.

15 Referring now to Figure 5 while continuing to refer generally to Figures 1-4, in
certain embodiments, a system 70 may include one or more admin computers 84 operably
connected, typically via structural cabling 78, to one or more nodes 74, shown in Figure 5
as workstations 74a-d. In the depicted embodiment, the system 70 also includes network
infrastructure devices 76a-c. The depicted system 70 also includes three network
infrastructure devices designated as devices 76a-c.

20 As shown, the admin computer 84, which may be a server 54, typically hosts an
admin module 86. In the depicted embodiment, the admin module 86 includes a monitoring
module 110 for monitoring the connection of devices to a network and changes in such
connections, a database module 112 for storing network device connection information, and
a correlation module 114 for associating network devices with network physical locations.
25 Workstations 74, such as workstations 74a-d, typically each host a reporting module 88 that
typically function to ascertain end point connection information 100 from the closest network

5 infrastructure device 76 with respect to the hosting workstation 74 and other local network
devices 90. Each reporting module 88 also typically reports such "endpoint connection
information" to the admin module 86 hosted on the admin computer 84. For example, in the
depicted embodiment, the network infrastructure device 76 closest to workstations 74c and
74d is network infrastructure device 76a, and the closest device 76 to workstation 74a is
10 network infrastructure device 76b.

Referring to Figure 6 while continuing to refer generally to Figures 1-5, an admin
computer 84 may include a processor 12 for executing executable data structures, memory
14 for storing executable and operational data structures, and a network card 26 for
connecting to a network 30 or other network. The memory device 14 of computer 84, may
15 store an operating system 13 and an admin module 86 for providing functionality in
accordance with the invention.

In the depicted embodiment, the admin module 86 may include a monitoring module
110, a database module 112, a correlation module 114, and an other module 115. In one
embodiment, the admin module 86, as every other module in accordance with the invention,
20 may be any thing from a single machine-level instruction, to an entire multimedia
application. That is, an individual module 86, 88, 110, 112, 114, and 115, including all sub-
modules thereof, can physically be stored in any size, shape, configuration, on any number
of computers, in order to execute its function. Thus, the monitoring module 110 is that code
that is logically executed in order to effect the monitoring process for obtaining copies of end
25 point connection information 100 for every device on the network and updating the copies
such end point connection information as devices are moved, added, and/or removed from

the network. Meanwhile, the database module is responsible for storing copies of end point connection information 100 corresponding to all network devices in device records 132 of a database 130.

The correlation module 114 is responsible for correlating or binding the device records 132 to infrastructure records 134, which store the details of the physical layout 105 of the network. Other modules 111 may be created to provide other services, or to support the monitoring, database, and correlation processes.

In certain embodiments, the admin module 86 may include a monitoring module 110. The monitoring module 110 may include a communication module 120 responsible for communicating with reporting modules 88, an inventory module 122 responsible for conducting a comprehensive inventory of devices connected to a network, and an update module 124 responsible for monitoring changes to the connection status of devices to a network. In other embodiments, a monitoring module 110 may also include a control module 126 for managing the functions of the monitoring module 110. Changes in connection status of devices to a network may include without limitation addition of devices, removal of devices, or movement of devices from a first physical or logical location on a network to a second such location.

In certain embodiments, the admin module 86 may include a database module 112. The database module 112 may either include, or may access outside itself, a database engine 136 for managing a database 130, which may include software license records 131, device records 132, infrastructure records 134, a binding table 135 or binding tables 135, and



5 product recognition records 137. Typically, the records 131, records 132, records 134, binding table 135, and records 137 constitute a database 130.

Meanwhile, a database system typically includes a standard, well known, reliable database engine 136 operating according to some schema to make, create, edit, retrieve, and otherwise manage database records 131, 132, 134, 135, 137. The software license records 131, device records 132, infrastructure records 134, binding table 135, and product recognition records 137 may be configured in numerous ways.

In general, the database engine 112 may be any commercial database engine, such as those produced under the current ODBC standards, the commercial products such as Oracle™, Sybase™, and others known in the art. The database records 131, 132, 134, 135, 137 may be those created in accordance with a schema, or hierarchy in any format, whether conventional, relational database, lists, object-oriented databases, or the like.

In certain embodiments, the admin module 86 may include a correlation module 114. A correlation module 114 may include a matching module 140 for binding network devices to physical layouts and a device recognition module 142 capable of recognizing a wide range of network devices. The matching module 140 may be responsible to present the device records 132 and infrastructure records 134 to a network system administrator, who can then match the device records 132 to the infrastructure records to create the binding table 135. Once the binding table 135 has been created for the system 70, the update module 124 of the monitoring module 110 may use information stored in the device records 132, the infrastructure records 134, and the binding table 135 to automatically update the database 130 as network devices are added, moved, and/or removed from the network.

5 In selected embodiments, the matching module 140 may also be responsible to
determine whether an organization possesses software licenses, as set forth in the software
license records 131, corresponding to software installed on nodes 74 and other network
devices 90. Accordingly, the matching module 140 may be configured to assess whether a
network site 72, for example, is running unauthorized software. Moreover, in certain
10 embodiments, the matching module 140 may be configured to use information stored in
product recognition records 137 to recognize network nodes 74, network devices 90, and/or
software installed on devices 74, 90. The matching module 140 may also be configured to
use information stored in the product recognition records 137 to obtain and store additional
information pertaining to recognized devices 74, 90. For example, the product recognition
15 records 137 may contain information regarding product nomenclature and/or features that
may be productively stored in selected device records 132.

Referring to Figure 7 while continuing to refer generally to Figures 1-6, a node
device 74 may include a processor 12 for executing executable data structures, memory 14
for storing executable and operational data structures, and a network card 26 for connecting
20 to a network 30 or other network. The memory device 14 of node 74, may store an operating
system 13 and a reporting module 88 for providing functionality in accordance with the
invention.

In certain embodiments, a reporting module 88 may include a control module 160 for
controlling the functions of reporting module 88, a communication module 162, a query
25 module 164, an inventory module 166, and an update module 167. The communication
module 162 may be responsible for receiving requests from the admin module 86 and

transmitting information, including without limitation end point connection information 100, to the admin module 86. The query module 164 may be responsible for obtaining end point connection information 100 from network infrastructure devices 76 pertaining to the node 74 and other local network devices 90.

The inventory module 166 may be responsible to identify network devices 90 local to the node 74 hosting the reporting module 88 and obtain end point connection information corresponding to such network devices 90. In certain embodiments, the inventory module 166 may also be responsible to detect and transmit software and hardware configuration information corresponding to a node 74 and other network devices 90. The update module 167 may detect changes in end point connection information 100 pertaining to the node 74 and identified local network devices 90.

In certain embodiments, a reporting module 88 of a node 74 may also store one or more temporary device records 170. A temporary device record 170 may include end point connection information 100 and other information pertaining to the node 74 and other local network devices 90. A temporary device record 170 may include all information requested by an admin module 86 to create or update device records 132 corresponding to nodes 74 and/or other network devices 90.

Referring now to both Figures 6 and 7, an admin module 86 and a reporting module 88 may be configured in any suitable arrangements to execute on one or more processors 12. Thus, distributed processing, client/server architectures, application server architectures, and the like may all be used, in order to host an admin module 86 and a reporting module 88. An admin module 86 and a reporting module 88 may include all the functionalities of an

apparatus and method in accordance with the invention. Typically, an admin module 86 interacts with a reporting module 88 in a server/client relationship wherein the reporting module 88 supports the admin module 86 by feeding particular individual functional processes or information to the admin module 86. Alternatively, the functions of an admin module 86 and a reporting module 88 could be hosted on a single computer 11 with the separate modules operating as a single software module.

Referring to Figures 8 while continuing to refer to Figure 4, each infrastructure record 180 of the infrastructure records 134 in accordance with the invention may include several fields that can uniquely identify a physical location at which a node 74 or other network device 90 is installed. For example, an infrastructure record 180 may include any or all of the following fields: a location identification field 182, a country field 184, a state/province field 186, a site name field 188, a site address field 190, a building identification field 192, a room identification field 194, a room position field 196, and other fields 198 that may be necessary or useful in uniquely identifying a physical location 108. In certain embodiments, not all of the foregoing fields are necessary to uniquely identify a physical location 108 of a network site 72 in accordance with the invention. In other embodiments, additional fields 198 may be necessary to uniquely identify a physical location 108.

Referring to Figure 9 while continuing to refer to Figures 1-8 generally, each device record 133 of the device records 132 in accordance with the invention may include several fields that store the end point connection information 100 corresponding to a node 74 or network device 90. For example, a device record 133 may include any or all of the following fields: a device identification number field 210, device end point connection information

field 211, a NIC number field 212, a device type field 214, a manufacturer field 216, a model field 218, a memory field 220, a disk space field 222, an attached devices field 224, an installed software field 226, a hardware nomenclature field 228, a registration status field 227, a last updated field 229, and other fields 230 that may store information necessary or useful in providing functionality in accordance with the invention.

Referring to Figures 9 and 10, in certain embodiments, a binding table 135 may be created as a result of the binding or associating of end point connection information 100 corresponding to a node 74 or other network device 90 to a physical location 108. In other words, the resulting binding or association between network devices 74, 90 and physical locations 108 may be stored in a binding table 135. Typically, a binding table 135 comprises a variety of records 242 including a port identification field 211 or port identifier field 211 and a location identification field 182 or location identifier field 182.

Referring to Figure 9, alternatively, a device record 133 may serve as a binding record 242 so long as a location identifier 182 is included in the device record 133, along with the device identifier 210. Accordingly, the device records 132 may function as a binding table 135 in accordance with the invention. In certain embodiments, a separate and distinct binding table 135, apart from the device records 132, may not, therefore, exist.

Referring to Figure 11, the database module 112 may be viewed and updated via a database user interface 244. In certain embodiments, a database user interface 244 may include an interface 246 for viewing and updating network infrastructure devices 76 and end point connection information 100 corresponding thereto. Moreover, a user interface 244 may include an interface 248 for viewing and updating network sites 72 and physical locations

108. In selected embodiments, a user interface 244 may also include an interface 250 for viewing and updating the binding or association between network devices 74, 90 and end point connection information 100.

Referring to Figure 12, a process 260 in accordance with the invention may include ascertaining 262 end point connection information 100 corresponding to one or more network devices 74, 90 connected to a network 30. The process may also include ascertaining 264 physical locations 108 corresponding to the network devices 74, 90 connected to the network 30. Once such end point connection information 100 and physical locations 108 are known, the end point connection information 100 may be bound 266 or associated 266 to the physical locations 108, typically resulting in a binding table 135. Subsequently, movements, additions, and/or deletions of devices 74, 90 may be tracked 268. Of course, network devices 74, 90 are often added 270 to typical networks 30.

Referring to Figure 13, one embodiment of a process 262 for ascertaining end point connection information may include a node 74 locating 280 the nearest network infrastructure device 76. The node 74 may query the network infrastructure device 76 to obtain 282 the port connection table 100 or end point connection information 100 corresponding to the network infrastructure device 76. The node 74 may then find 284 the particular end point connection information 100 corresponding to the node 74, which is typically an identifier to a particular port 80 of the network infrastructure device 76 to which the node 74 is connected via structural cabling 78. The node 74 may also find 286 the end point connection information 100 corresponding to other network devices 90 local to the node 74, which again is typically an identifier to a particular port 80 or ports 80 of the

5 network infrastructure device to which the network devices 90 are connected via structural cabling 78. The node 74 may then transfer 288 the collected end point connection information to the central database 112 for storage in the device records 132 thereof.

Referring to Figure 14, one embodiment of a process 266 for binding end point connection information 100 to physical locations 108 may include providing 290 an end point connection information database, which information is typically stored in the device records 132 of the database 112. The process 266 may also include providing 292 a physical location database, which information is typically stored in the infrastructure records 134 of the database 112. Moreover, the process 266 may include binding 294 individual device records, each containing end point connection information corresponding to a network device 74, 90, to individual infrastructure records 134 to form a binding table 135.

Referring to Figure 14, one embodiment of a process 268 for tracking movements of network devices 74, 90 may include the movement 300 of a network device 74, 90. Upon such movement of a node 74, the node 74 may ascertain 302 the new end point connection information 100 corresponding to the node 74. Upon such movement of an other network device 90, a node 74 local to the network device 90 may ascertain 302 the new end point connection information 100 corresponding to the network device 90. Such node 74 may then transfer 304 the new end point connection information 100 corresponding to the device 74, 90 to the corresponding device record 133. Based on information contained in the binding table 135, the device 74, 90 would automatically be bound to the physical location 108 corresponding to the new end point connection information 100.

5

The present invention may be embodied in other specific forms without departing from its spirit or essential characteristics. The described embodiments are to be considered in all respects only as illustrative, and not restrictive. The scope of the invention is, therefore, indicated by the appended claims, rather than by the foregoing description. All changes which come within the meaning and range of equivalency of the claims are to be embraced within their scope.

10

What is claimed and desired to be secured by United States Letters Patent is:

11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039 1040 1041 1042 1043 1044 1045 1046 1047 1048 1049 1050 1051 1052 1053 1054 1055 1056 1057 1058 1059 1060 1061 1062 1063 1064 1065 1066 1067 1068 1069 1070 1071 1072 1073 1074 1075 1076 1077 1078 1079 1080 1081 1082 1083 1084 1085 1086 1087 1088 1089 1090 1091 1092 1093 1094 1095 1096 1097 1098 1099 1100 1101 1102 1103 1104 1105 1106 1107 1108 1109 1110 1111 1112 1113 1114 1115 1116 1117 1118 1119 1120 1121 1122 1123 1124 1125 1126 1127 1128 1129 1130 1131 1132 1133 1134 1135 1136 1137 1138 1139 1140 1141 1142 1143 1144 1145 1146 1147 1148 1149 1150 1151 1152 1153 1154 1155 1156 1157 1158 1159 1160 1161 1162 1163 1164 1165 1166 1167 1168 1169 1170 1171 1172 1173 1174 1175 1176 1177 1178 1179 1180 1181 1182 1183 1184 1185 1186 1187 1188 1189 1190 1191 1192 1193 1194 1195 1196 1197 1198 1199 1200 1201 1202 1203 1204 1205 1206 1207 1208 1209 1210 1211 1212 1213 1214 1215 1216 1217 1218 1219 1220 1221 1222 1223 1224 1225 1226 1227 1228 1229 1230 1231 1232 1233 1234 1235 1236 1237 1238 1239 1240 1241 1242 1243 1244 1245 1246 1247 1248 1249 1250 1251 1252 1253 1254 1255 1256 1257 1258 1259 1260 1261 1262 1263 1264 1265 1266 1267 1268 1269 1270 1271 1272 1273 1274 1275 1276 1277 1278 1279 1280 1281 1282 1283 1284 1285 1286 1287 1288 1289 1290 1291 1292 1293 1294 1295 1296 1297 1298 1299 1300 1301 1302 1303 1304 1305 1306 1307 1308 1309 1310 1311 1312 1313 1314 1315 1316 1317 1318 1319 1320 1321 1322 1323 1324 1325 1326 1327 1328 1329 1330 1331 1332 1333 1334 1335 1336 1337 1338 1339 1340 1341 1342 1343 1344 1345 1346 1347 1348 1349 1350 1351 1352 1353 1354 1355 1356 1357 1358 1359 1360 1361 1362 1363 1364 1365 1366 1367 1368 1369 1370 1371 1372 1373 1374 1375 1376 1377 1378 1379 1380 1381 1382 1383 1384 1385 1386 1387 1388 1389 1390 1391 1392 1393 1394 1395 1396 1397 1398 1399 1400 1401 1402 1403 1404 1405 1406 1407 1408 1409 1410 1411 1412 1413 1414 1415 1416 1417 1418 1419 1420 1421 1422 1423 1424 1425 1426 1427 1428 1429 1430 1431 1432 1433 1434 1435 1436 1437 1438 1439 1440 1441 1442 1443 1444 1445 1446 1447 1448 1449 1450 1451 1452 1453 1454 1455 1456 1457 1458 1459 1460 1461 1462 1463 1464 1465 1466 1467 1468 1469 1470 1471 1472 1473 1474 1475 1476 1477 1478 1479 1480 1481 1482 1483 1484 1485 1486 1487 1488 1489 1490 1491 1492 1493 1494 1495 1496 1497 1498 1499 1500 1501 1502 1503 1504 1505 1506 1507 1508 1509 1510 1511 1512 1513 1514 1515 1516 1517 1518 1519 1520 1521 1522 1523 1524 1525 1526 1527 1528 1529 1530 1531 1532 1533 1534 1535 1536 1537 1538 1539 1540 1541 1542 1543 1544 1545 1546 1547 1548 1549 1550 1551 1552 1553 1554 1555 1556 1557 1558 1559 1560 1561 1562 1563 1564 1565 1566 1567 1568 1569 1570 1571 1572 1573 1574 1575 1576 1577 1578 1579 1580 1581 1582 1583 1584 1585 1586 1587 1588 1589 1590 1591 1592 1593 1594 1595 1596 1597 1598 1599 1600 1601 1602 1603 1604 1605 1606 1607 1608 1609 1610 1611 1612 1613 1614 1615 1616 1617 1618 1619 1620 1621 1622 1623 1624 1625 1626 1627 1628 1629 1630 1631 1632 1633 1634 1635 1636 1637 1638 1639 1640 1641 1642 1643 1644 1645 1646 1647 1648 1649 1650 1651 1652 1653 1654 1655 1656 1657 1658 1659 1660 1661 1662 1663 1664 1665 1666 1667 1668 1669 1670 1671 1672 1673 1674 1675 1676 1677 1678 1679 1680 1681 1682 1683 1684 1685 1686 1687 1688 1689 1690 1691 1692 1693 1694 1695 1696 1697 1698 1699 1700 1701 1702 1703 1704 1705 1706 1707 1708 1709 1710 1711 1712 1713 1714 1715 1716 1717 1718 1719 1720 1721 1722 1723 1724 1725 1726 1727 1728 1729 1730 1731 1732 1733 1734 1735 1736 1737 1738 1739 1740 1741 1742 1743 1744 1745 1746 1747 1748 1749 1750 1751 1752 1753 1754 1755 1756 1757 1758 1759 1760 1761 1762 1763 1764 1765 1766 1767 1768 1769 1770 1771 1772 1773 1774 1775 1776 1777 1778 1779 1780 1781 1782 1783 1784 1785 1786 1787 1788 1789 1790 1791 1792 1793 1794 1795 1796 1797 1798 1799 1800 1801 1802 1803 1804 1805 1806 1807 1808 1809 1810 1811 1812 1813 1814 1815 1816 1817 1818 1819 1820 1821 1822 1823 1824 1825 1826 1827 1828 1829 1830 1831 1832 1833 1834 1835 1836 1837 1838 1839 1840 1841 1842 1843 1844 1845 1846 1847 1848 1849 1850 1851 1852 1853 1854 1855 1856 1857 1858 1859 1860 1861 1862 1863 1864 1865 1866 1867 1868 1869 1870 1871 1872 1873 1874 1875 1876 1877 1878 1879 1880 1881 1882 1883 1884 1885 1886 1887 1888 1889 1890 1891 1892 1893 1894 1895 1896 1897 1898 1899 1900 1901 1902 1903 1904 1905 1906 1907 1908 1909 1910 1911 1912 1913 1914 1915 1916 1917 1918 1919 1920 1921 1922 1923 1924 1925 1926 1927 1928 1929 1930 1931 1932 1933 1934 1935 1936 1937 1938 1939 1940 1941 1942 1943 1944 1945 1946 1947 1948 1949 1950 1951 1952 1953 1954 1955 1956 1957 1958 1959 1960 1961 1962 1963 1964 1965 1966 1967 1968 1969 1970 1971 1972 1973 1974 1975 1976 1977 1978 1979 1980 1981 1982 1983 1984 1985 1986 1987 1988 1989 1990 1991 1992 1993 1994 1995 1996 1997 1998 1999 2000 2001 2002 2003 2004 2005 2006 2007 2008 2009 2010 2011 2012 2013 2014 2015 2016 2017 2018 2019 2020 2021 2022 2023 2024 2025 2026 2027 2028 2029 2030 2031 2032 2033 2034 2035 2036 2037 2038 2039 2040 2041 2042 2043 2044 2045 2046 2047 2048 2049 2050 2051 2052 2053 2054 2055 2056 2057 2058 2059 2060 2061 2062 2063 2064 2065 2066 2067 2068 2069 2070 2071 2072 2073 2074 2075 2076 2077 2078 2079 2080 2081 2082 2083 2084 2085 2086 2087 2088 2089 2090 2091 2092 2093 2094 2095 2096 2097 2098 2099 2100 2101 2102 2103 2104 2105 2106 2107 2108 2109 2110 2111 2112 2113 2114 2115 2116 2117 2118 2119 2120 2121 2122 2123 2124 2125 2126 2127 2128 2129 2130 2131 2132 2133 2134 2135 2136 2137 2138 2139 2140 2141 2142 2143 2144 2145 2146 2147 2148 2149 2150 2151 2152 2153 2154 2155 2156 2157 2158 2159 2160 2161 2162 2163 2164 2165 2166 2167 2168 2169 2170 2171 2172 2173 2174 2175 2176 2177 2178 2179 2180 2181 2182 2183 2184 2185 2186 2187 2188 2189 2190 2191 2192 2193 2194 2195 2196 2197 2198 2199 2200 2201 2202 2203 2204 2205 2206 2207 2208 2209 2210 2211 2212 2213 2214 2215 2216 2217 2218 2219 2220 2221 2222 2223 2224 2225 2226 2227 2228 2229 2230 2231 2232 2233 2234 2235 2236 2237 2238 2239 2240 2241 2242 2243 2244 2245 2246 2247 2248 2249 2250 2251 2252 2253 2254 2255 2256 2257 2258 2259 2260 2261 2262 2263 2264 2265 2266 2267 2268 2269 2270 2271 2272 2273 2274 2275 2276 2277 2278 2279 2280 2281 2282 2283 2284 2285 2286 2287 2288 2289 2290 2291 2292 2293 2294 2295 2296 2297 2298 2299 2300 2301 2302 2303 2304 2305 2306 2307 2308 2309 2310 2311 2312 2313 2314 2315 2316 2317 2318 2319 2320 2321 2322 2323 2324 2325 2326 2327 2328 2329 2330 2331 2332 2333 2334 2335 2336 2337 2338 2339 2340 2341 2342 2343 2344 2345 2346 2347 2348 2349 2350 2351 2352 2353 2354 2355 2356 2357 2358 2359 2360 2361 2362 2363 2364 2365 2366 2367 2368 2369 2370 2371 2372 2373 2374 2375 2376 2377 2378 2379 2380 2381 2382 2383 2384 2385 2386 2387 2388 2389 2390 2391 2392 2393 2394 2395 2396 2397 2398 2399 2400 2401 2402 2403 2404 2405 2406 2407 2408 2409 2410 2411 2412 2413 2414 2415 2416 2417 2418 2419 2420 2421 2422 2423 2424 2425 2426 2427 2428 2429 2430 2431 2432 2433 2434 2435 2436 2437 2438 2439 2440 2441 2442 2443 2444 2445 2446 2447 2448 2449 2450 2451 2452 2453 2454 2455 2456 2457 2458 2459 2460 2461 2462 2463 2464 2465 2466 2467 2468 2469 2470 2471 2472 2473 2474 2475 2476 2477 2478 2479 2480 2481 2482 2483 2484 2485 2486 2487 2488 2489 2490 2491 2492 2493 2494 2495 2496 2497 2498 2499 2500 2501 2502 2503 2504 2505 2506 2507 2508 2509 2510 2511 2512 2513 2514 2515 2516 2517 2518 2519 2520 2521 2522 2523 2524 2525 2526 2527 2528 2529 2530 2531 2532 2533 2534 2535 2536 2537 2538 2539 2540 2541 2542 2543 2544 2545 2546 2547 2548 2549 2550 2551 2552 2553 2554 2555 2556 2557 2558 2559 2560 2561 2562 2563 2564 2565 2566 2567 2568 2569 2570 2571 2572 2573 2574 2575 2576 2577 2578 2579 2580 2581 2582 2583 2584 2585 2586 2587 2588 2589 2590 2591 2592 2593 2594 2595 2596 2597 2598 2599 2600 2601 2602 2603 2604 2605 2606 2607 2608 2609 2610 2611 2612 2613 2614 2615 2616 2617 2618 2619 2620 2621 2622 2623 2624 2625 2626 2627 2628 2629 2630 2631 2632 2633 2634 2635 2636 2637 2638 2639 2640 2641 2642 2643 2644 2645 2646 2647 2648 2649 2650 2651 2652